

| Rundstähle Gewalzt und geschmiedet, normalisiert, vorgedreht EN 10060 - DIN 7527/6 | | | | |
|--|-------|--------|--------|--------|
| 10 mm | 33 mm | 75 mm | 180 mm | 380 mm |
| 12 mm | 34 mm | 80 mm | 190 mm | 390 mm |
| 13 mm | 35 mm | 85 mm | 200 mm | 400 mm |
| 14 mm | 36 mm | 90 mm | 210 mm | 420 mm |
| 15 mm | 38 mm | 95 mm | 220 mm | 430 mm |
| 16 mm | 40 mm | 100 mm | 230 mm | 450 mm |
| 18 mm | 42 mm | 105 mm | 240 mm | 480 mm |
| 19 mm | 45 mm | 110 mm | 250 mm | 500 mm |
| 20 mm | 46 mm | 115 mm | 260 mm | 520 mm |
| 21 mm | 48 mm | 120 mm | 270 mm | 530 mm |
| 22 mm | 50 mm | 125 mm | 280 mm | 550 mm |
| 23 mm | 52 mm | 130 mm | 290 mm | 580 mm |
| 24 mm | 53 mm | 135 mm | 300 mm | 600 mm |
| 25 mm | 55 mm | 140 mm | 310 mm | 650 mm |
| 26 mm | 56 mm | 145 mm | 320 mm | 700 mm |
| 27 mm | 58 mm | 150 mm | 330 mm | 800 mm |
| 28 mm | 60 mm | 155 mm | 340 mm | |
| 29 mm | 63 mm | 160 mm | 350 mm | |
| 30 mm | 65 mm | 165 mm | 360 mm | |
| 32 mm | 70 mm | 170 mm | 370 mm | |